

**DECLARATION OF COMPATIBILITY
Service Conditions**

Nr. 20/03

1. The trade name of the construction product:

Series SENA

DN: 8; 10; 15; 20 ; 25; 32; 40; 50; 65; 80; 100

2. Type designation of a construction product:

Ball valve

Connection dimensions: $\frac{1}{4}$, $\frac{3}{8}$, $\frac{1}{2}$; $\frac{3}{4}$; 1; $1\frac{1}{4}$; $1\frac{1}{2}$; 2; $2\frac{1}{2}$; 3; 4

3. Name and address of the manufacturer of the product:

VÁLVULAS ARCO S.L. Avda de Cid 16, Foios 46134 Valencia, Spain

4. Main intended use:

SENA series are manually operated metallic ball valve for use as shut-off valves for closing and opening flow in plumbing network. Fluid: Drinking water and hot water. Nominal pressure (PN) 30 bar. Temperature range from -20°C up to 120°C, excluding frozen. They can work only in two positions: completely closed or completely open, they should not be used for flow regulation. The valves can be used in any position of the flow channel axis, vertically, horizontally or at an angle.

5. Other uses:

SENA series can also be used with water and a **maximum of 50% glycol**. In this use, the mixing fluid is **prohibited as water for human consumption**.

A blue ink signature, likely of Carlos López, consisting of stylized loops and a horizontal line.

26 February 2020
Valencia, SPAIN

Carlos López
Product Engineering Manager